

A large, abstract green watercolor splash graphic that occupies the right side of the page, with various shades of green and blue.

WETAN FAST
Wetting and oil remover Agent

TECHNICAL DATA SHEET



WETAN FAST Wetting and oil remover Agent

Product Features

Ionic Structure	Anionic
Appearance	Colorless, clear liquid.
pH Range	5.0-8.0

- Wetting and oil remover agent for cotton and cotton/elastane blends. It is especially used in degreasing processes of tightly woven fabrics. It provides fast and homogeneous extraction of the bath content in padding applications. It is foamless and provides ease of use. It is resistant to hard waters, acids, alkalis, oxidative substances, reductive substances and electrolytes. It can be used in the same environment with nonionic and anionic substances.

Application Information

Pre-oil removal processes of cotton products

Wetan FAST	1.0-3.0 gr/lit
Soda	2.0 gr/lit
Temperature	80 C
Duration	20-30 min

Bleaching of cotton products

Wetan FAST	0.5-1.0 gr/lit
CAUSTIC	2.0-6.0 gr/lit
PEROXIDE	2.0-8.0 gr/lit
Temperature	98 C

In PAD-BATCH dyeing processes:

Wetan FAST	1.0 - 4.0 gr/lit
------------	------------------

STORAGE: Storage life is 12 months in its original packaging and at room temperature.

PACKAGING : 120kg drum and 1000 kg IBC